



## ANTHRACITE GREY

Solid colour

Warranty

**10 YEARS**

Application temperature

**FROM +15°C TO +25°C**

Storage from +5°C to +35°C

**3 YEARS**

**LENGTH** ↔ **50 m**

**WIDTH** ↔ **122 cm**

Primer/Primer +	✓	CE	✓
Kraft paper release liner	✓	IMO	✓
Stretchable	✓	MED	✓
Calendered polymeric	✓	RAIL	✓
Interior installation	✓	REACH	✓
Outside installation	✗	TCHIBO	✓
UV-Resistant	✓	TABER TEST	✓
Permanent Air Release	✓	VOC	✓
Adhesive			
Appearance	Mat		
Thickness	210 μ		
Scratch-proof	Low		

### ADHESIVE STRENGTH :

91 minutes after installation 1.04 Kg/cm  
24 hours after installation: 1.43 Kg/cm  
3 days after installation: 1.51 Kg/cm  
7 days after installation: 1.65kg/cm

### ADHESIVE STRENGTH AT HIGH TEMPERATURE :

After the 1st day: 1.37 Kg/cm  
After 7 days: 1.03 Kg/cm

### DURABILITY :

This product offers exceptional resistance to water, dirt, abrasion, UV rays and wear (yellowing, crackling, scaling, delamination).

### MAINTENANCE :

For daily care and maintenance of the film use only neutral pH detergents, do not use products with too much acidic or basic pH.

- Hot water (not boiling) can help eliminate stubborn stains
- In some cases, even a solution based on isopropyl alcohol and water can be effective (70% ISO 30% H2O. Not on printed Cover Styl')
- Use only soft cloths or sponges to clean the vinyl (except glitter)
- If persistent stains are present it means that care and maintenance have not been performed correctly. In this case carry out a repair with patch (not guaranteed but effective and economical) or complete replacement of the vinyl;
- Don't use any organic-based cleaning product like ammonia or polish to clean vinyl